MV++ v. 1.5a

Matrix / Vector Class
Reference Guide

April 1996

Roldan Pozo

Applied and Computational Mathematics Division
National Institute of Standards and Technology

Contents

1 Overview **1**
1.1 About MV++ . . . 1
1.2 Basic Features . . . 1
1.3 MV++ Classes . . . 3
1.3.1 Templated class version . . . 3
1.3.2 Non-templated class version . . . 3
1.4 References . . . 4

2 Reference Manual **5**
MV_Vector . . . 5
MV_VecIndex . . . 10
MV_ColMat . . . 13

Chapter 1

Overview

1.1 About MV++

MV++ is a small, efficient set of concrete vector and matrix classes specifically designed for high performance numerical computing.

The MV++ package includes interfaces to the computational kernels found in the Basic Linear Algebra Subprograms (BLAS), such as scalar updates, vector sums, and dot products. The idea behind MV++ is to leverage vendor-supplied or optimized BLAS routines that are fine-tuned for particular platforms.

The various MV++ classes form the building blocks of larger user-level libraries such as SparseLib++[2] and LAPACK++[1]. The MV++ library was built to supply simple, concrete, **numerical** vector and column oriented dense matrix classes. These classes are designed to provide:

- **minimal overhead** in constructing, assigning, and copying vectors and matrices
- **performance** competitive with optimized Fortran kernels
- data structure **compatibility** with Fortran libraries and subroutines
- support for generic element types through **templated** parameters
- support for operations with contiguous **subvectors** and **submatrices** (e.g. zeroing out a section of a vector)
- optional runtime support for **array-bounds checking**

1.2 Basic Features

MV++ provides two basic classes: a numerical vector (1-d array), and column (Fortran) oriented dense matrix. Indexing is performed via the `operator()`, as in `A(i,j)`.

Subvectors and submatrices can be accessed through `MV_VecIndex` classes. In other words, if B is the vector

$$\{0.0,\ 0.1,\ 0.2,\ 0.3,\ 0.4,\ 0.5,\ 0.6\}$$

then `B(MV_VecIndex(1,5)) = 9.9` sets B to

$$B = \{0.0,\ 0.1,\ 9.9,\ 9.9,\ 9.9,\ 9.9,\ 9.9,\ 0.6\}$$

and is equivalent to

```
for (i=1; i<=5; B[i++] = 9.9 )
```

Other considerations:

- Support is provided only for unit strides (for efficient indexing).
- Indexing is as fast as native C arrays.
- "Copy-by-value" semantics are used.
- Optional "share" semantics are available, allowing vectors to be constructed as "views", or "references" of an existing memory. To create a view of (or reference to) an existing MV++ matrix or vector, use

  ```
  MV_Vector_double A( &d[0], n, MV_Vector_::ref );
  ```

  This allows one to construct vectors as views of any contiguous C array. It will not release the memory space when the vector is destroyed or goes out of scope. Vector views can assign and reference sections of vector, but cannot modify their *size*.
- Block-range indexing is supported via MV_VecIndex class (e.g. A(I) = B;). Note that for this to work, A(I) must return a vector view.
- Optional range checking is available via a compile switch.
- Support is provided for both [] and () style indexing for vectors, and () for matrices.
- Function code for the () and [] operators has been inlined into the class declaration for compilers that refuse to inline otherwise.
- Loop unrolling (depth=4) is used for copying and assigning vectors. Therefore, on some machines it may be faster to execute A=scalar, rather than manually assigning a native C array using an explicit for loop:

  ```
  for (i=0; i<N; d[i++] = scalar);
  ```

1.3 MV++ Classes

MV++ supports both templated and non-templated vector and matrix classes. Non-templated versions of the classes are useful when using C++ compilers that do not provide full support for template instantiations (several compilers have problems using templates in applications linked with multiple .o files), or when large template header files begin to seriously affect compilation.

1.3.1 Templated class version

Templated MV++ vectors are denoted as `MV_Vector<type>` in `./include/mvvtp.h`. Matrices are denoted as `MV_ColMat<type>` in `./include/mvmtp.h`.

Typical use is illustrated by an example:

```
#include "mvmtp.h"

// ...

class MyObject {  // ...  };

MV_ColMat<MyObject> A(m, n);
MV_Vector<MyObject> B(n), C(n);
```

The only requirement on the class `MyObject` is that `MyObject` objects are closed under the operations `+`, `*`, `/`, and `-`.

1.3.2 Non-templated class version

Non-templated classes in MV++ have names such as `MV_Vector_double` and `MV_MatCol_int`. By default, the initial installation supports

- `MV_Vector_double`
- `MV_Vector_float`
- `MV_Vector_int`
- `MV_Vector_complex`
- `MV_ColMat_double`
- `MV_ColMat_float`
- `MV_ColMat_int`

- `MV_ColMat_complex`

In general, the class corresponding to the templated equivalent of `XX<t>` is denoted as `XX_t`.

Type specific versions the MV++ classes are generated from the same "base" file via an editor or simple preprocessor, such as `sed`. For example, `mvvt.h` defines a class of

```
class MV_Vector_$TYPE
{
   protected:
        $TYPE *p_;
        ...
}
```

By creating a copy of this file in which every occurrence of "$TYPE" is changed to the name of a user-specific class, one can create MV++ vectors out of any numerical object which forms an algebraic field. The simple command,

```
sed '1,$s/\$TYPE/MyObject/g' mvv.h > mvv_MyObject.h
```

will create an MV++ vector of `MyObjects`. Similarly, one can create the accompanying `mvv_MyObject.cc` file from the `mvv.cc` base in the `/src` directory. [1]

1.4 References

[1] J. J. Dongarra, R. Pozo, D. Walker, "LAPACK++: A Design Overview of Object-Oriented Extensions for High Performance Linear Algebra," Proceedings of Supercomputing '93, IEEE Press, 1993, pp. 162-171.

[2] J. J. Dongarra, A. Lumsdaine, R. Pozo, K. A. Remington, "A Sparse Matrix Library in C++ for High Performance Architectures," Proceedings of the Object Oriented Numerics Conference, 1994, pp. 214-218.

[1] Use a preprocessor that can also change substring expressions, since the $TYPE expression occurs as part of the class name.

Chapter 2

Reference Manual

Name

MV_Vector

Description

One-dimensional vector storage class with minimal overhead. It is one step above a C array; it utilizes copy-by-value semantics, provides for unit-stride referencing and indexing using *(start, end)* pairs.

- deep-copy (optimized)
- only a container class, no mathematical operations defined yet.
- unit stride (elements are in contiguous memory locations)
- fixed 0-based offset
- $A(i)$ declared `inline` for efficiency

Major differences between original LAPACK++ vector class and MV++

- templated
- copy-by-value, rather than share-semantics
- much faster A(i) indexing, since indices always have unit stride.
- only *one* owner of data, but maybe various references, so no reference-counting scheme is used.

Declaration

#include < mvvtp.h >

MV_Vector<TYPE>()

Construct a null vector of zero length.

MV_Vector<TYPE>(int n = 0)

Construct a vector of length n, ($n \geq 0$). A vector of length zero is perfectly legal and usually termed a *null* vector. MV_Vector elements are UNINITIALIZED.

MV_Vector<TYPE>(int n, double s)

Construct a vector of length n and initialize all elements to the scalar value s.

MV_Vector<TYPE>(double * x, int n)

Construct a n-length vector as a new **copy** of an existing C/C++ array.

MV_Vector<TYPE>(double * d, int n, MV_Vector_::ref)

Construct a n-length vector as a **view** (share semantics) of an existing C/C++ array. Further changes to elments of `d` will be reflected in `MV_Vector<TYPE>`. Data space `d` will **not** be destroyed when calling `MV_Vector<TYPE>`.

MV_Vector<TYPE>(const MV_Vector<TYPE>& V)

Create a new n-length vector as a copy of an existing `MV_Vector<TYPE>`.

~MV_Vector<TYPE>()

Reclaim vector memory space if this the only structure using it.

Assignments

MV_Vector<TYPE>& operator=(const MV_Vector<TYPE>& V)

If `*this` is a reference then **inject()** left-hand side (V) into existing memory (both sides must conform). Otherwise, `*this` owns its data space, so delete it and create a new copy of `V`. (If conformant with `V`, then just copy in place.) Return reference to `*this` view.

MV_Vector<TYPE>& operator=(double s)

Set elements of left-hand size to the scalar value s.

MV_Vector<TYPE>& inject(const MV_Vector<TYPE>& V)

Copy elements of `V` into the memory space referenced by the left-hand side, without first releasing it. The effect is that if other vectors share memory with left-hand side, they too will be affected. Note that the length of `V` must be same be the same as that of the left-hand side vector.

MV_Vector<TYPE>& copy(MV_Vector<TYPE>& V)

Release left-hand side and copy elements of `V`. Unlike `MV_Vector<TYPE>::inject()` it does not require conformity, and previous references of left-hand side are unaffected.

int newsize(int n)

Resize to a *new* vector of length n. The element values are UNINITIALIZED, even if n is less than the current vector length.

Access Functions

TYPE& operator ()(int i)

Return ith element of vector, with zero-based offset. Optional runtime bounds checking ($0 \leq i \leq n$) set by compile time macro `MV_VECTOR_BOUNDS_CHECK`.

TYPE& operator [ ](int i)

Identical to `MV_Vector<TYPE>::operator()` above. Included mainly for compatibility to C/C++ `[]` syntax.

TYPE& operator ( )(const MV_VecIndex &I)

Returns a reference (view) of this vector specified by the ranges in `MV_VecIndex`.

For example, the following statements

```
MV_Vector<int> A(20), B(30);
MV_VecIndex I(0,3), J(7,10);

A(I) = B(J);
```

assign the first four elements of A to the values of `B(7)` through `B(10)`.

Information Functions

int size()

Return the length, n, of the vector.

int null()

Shorthand to test if zero-length vector. Identical to `(size()==0)`.

`int ref()`

return 1 if vector is a view (reference) to another vector or C array, zero otherwise.

Macros

`MV_VECTOR_BOUNDS_CHECK`

Optional compile time macro, to perform bounds checking ($0 \leq i \leq n$) in a n-length vector. The default is NOT to perform this check (this is consistent with C/C++); however, it is **highly recommended**, particularly during initial phases of development, testing, and debugging. There is a performance penalty for this, (essentially a boolean test at each element reference) so it can turned off for production runs, where performance may be critical.

I/O Functions

`ostream& operator ≪(ostream& s, const MV_Vector<TYPE>& V)`

Print vector, one element per line.

See also MV_ColMat

Name

MV_VecIndex : a contiguous subrange of MV_Vector elements.

Description

`MV_VecIndex` is an integer pair denoting the start and ending indices of a vector view. Only supports unit strides, so there is no *increment* argument. As an example, if B is the vector

$$\{0.0,\ 0.1,\ 0.2,\ 0.3,\ 0.4,\ 0.5,\ 0.6\}$$

then `B(MV_VecIndex(1,5)) = 9.9` sets B to

$$B = \{0.0,\ 0.1,\ 9.9,\ 9.9,\ 9.9,\ 9.9,\ 9.9,\ 0.6\}$$

and is equivalent to

```
for (i=1; i<=5; B[i++] = 9.9 )
```

Declaration

#include <mvvind.h>

MV_VecIndex()

Construct a null index (start=end=-1). Used to denote the complete vector range. For example,

```
B(MV_VecIndex()) = A;
```

will set all elements of B to those of A. This is equivalent to writing

```
B(MV_VecIndex(0,B.size()-1) = A;
```

or

```
B() = A;
```

or

```
for (i=0; i<N; i++)
  B(i) = A(i);
```

MV_VecIndex(unsigned int i, unsigned int j)

Construct an index range starting from position `i` through `j`. Conditions: $0 \leq i \leq j$.

MV_VecIndex(unsigned int i)

Construct an index range consisting of a single position, `i`. Used mainly for converting integers into MV_VecIndex's.

int start()

Returns the first index of the index range, (0 if MV_VecIndex is set to `all()`).

int end()

Returns the end of index range, or -1 if MV_VecIndex is set to `all`.

int length()

Returns the number of elements in index range, or -1 if MV_VecIndex is set to `all()`.

MV_VecIndex& operator+=(int i)

moves index range up by `i` elements. For example,

```
MV_VecIndex I(1:10);
I+= 3;
```

reset `I` to be $(4:13)$.

MV_VecIndex operator+(int i)

creates new index whose range is moved up by `i` elements. For example,

```
MV_VecIndex I(1:10);
MV_VecIndex K = I+3;
```

sets `K` to be $(4:13)$.

`MV_VecIndex operator-(int i)`

creates new index whose range is moved down by `i` elements,

`MV_VecIndex& operator-=(int i)`

moves index range down by `i` elements.

Name

MV_ColMat : column oriented (Fortran) templated dense matrix.

Description

A two-dimensional version of `MV_Vector<TYPE>`. Storage is column oriented, compatible as an argument to Fortran libraries.

- uses (deep) copy semantics
- indexing via `A(i,j)` where i, j are either integers or `MV_VecIndex` indices.
- supports only contiguous submatrices
- utilizes `Vector<TYPE>` container class
- has basic BLAS++ math functionality
- optimized to avoid memory copies when returning temporary `MV_ColMat<TYPE>` results by value from functions

Declaration

#include <mvvtp.h>

MV_ColMat<TYPE>()

Construct a null $0x0$ matrix.

MV_ColMat<TYPE>(int m, int n)

Construct a column-major matrix of size $m \times n$, $(m, n \geq 0)$. Matrix elements are UNINITIALIZED.

MV_ColMat<TYPE>(int m, int n, const TYPE& s)

Construct a column-major matrix of size $m \times n$, $(m, n \geq 0)$, and initialize matrix elments to the scalar s.

MV_ColMat<TYPE>(TYPE * v, int m, int n)

Construct a $m \times n$ matrix by copying the values from a one-dimensional C/C++ array of length mn.

MV_ColMat<TYPE>(TYPE * v, int m, int n, MV_ColMat_::ref)

Construct a $m \times n$ column-oriented matrix as a *view* of existing C array (length $m \times n$).

`MV_ColMat<TYPE>(const MV_ColMat<TYPE>& V)`

Create a new n-length vector from an existing one by copying.

`int newsize(int m, int n)`

Resize to a *new* matrix of size $m \times n$. The element values are UNINITIALIZED, even if resizing to a smaller matrix.

`~MV_ColMat<TYPE>()`

Destroy matrix and reclaim vector memory space if this the only structure using it.

Assignments

`MV_ColMat<TYPE>& operator=(const MV_ColMat<TYPE>& M)`

Release left-hand side (reclaiming memory space if possible) and construct a new copy of `V`. Return reference to new copy.

`MV_ColMat<TYPE>& operator=(const TYPE& s)`

Set elements of left-hand size to the scalar value s. No new matrix is created, so that if there other matrices that may reference this memory space will also be affected.

Access Functions

`TYPE& operator ( )(int i, int j)`

Return (i, j)th element of vector, with zero-based offset. Optional runtime bounds checking $(0 \leq i \leq m)$, $(0 \leq j \leq n)$, set by compile time macro `MV_MATRIX_BOUNDS_CHECK`.

TYPE& operator ( )(MV_VecIndex I, MV_VecIndex J)

Return submatrix view specified by indices `I` and `J`. (See `MV_VecIndex` class.) These indices specify start, increment, and ending offsets, similar to triplet notation of Matlab or Fortran 90. For example, if `B` is a 10×10 matrix, `I` is `(0:1)` and `J` is `(3:4)`, then `B(I,J)` denotes the 2×2 matrix

$$\begin{bmatrix} b_{0,3} & b_{0,4} \\ b_{0,4} & b_{1,4} \end{bmatrix}$$

.

Information Functions

int size(int d)

Return the length, n, of the dth dimension, i.e. for an $M \times N$ matrix `size(0)` returns M and `size(1)` returns N.

int lda()

Return the leading dimension of this matrix ($>= M$).

int ref()

Returns 1 if this matrix is a view to another C/C++ array.

Macros

MV_MATRIX_BOUNDS_CHECK

Compile time macro, either defined or undefined to perform bounds checking on matrix indexing operations. The default is NOT to perform this check (this is consistent with C/C++); however, it is **highly recommended** to utilize this check – particularly during initial phases of development, testing, and debugging. There is a performance penalty for this, (essentially a boolean test at each element reference) so it can turned off for production runs, where performance may be critical.

I/O Functions

friend ostream& operator *ll*(ostream& s, const MV_ColMat<TYPE>& V)

Print matrix (one row perline), with elements separated by white space.

See also MV_Vector<TYPE>, MV_VecIndex